[REGISTERED OFFICE ONLY]
The Levels
Capital Business Park
Cardiff
CF3 2PX
02920 099 098
sales@thisiswholesale.co.uk | https://www.onlineb2b.co.uk/

60W 24V DC LED Driver / LED Power Supply / LED Transformer - 2.5Amp 2.5A Constant Voltage LED Power Supply IP21 Indoor

£18.50



Product Description

NEW SLIM DESIGN! FITS THROUGH MOST DOWNLIGHT HOLES.
DIMENSIONS: 150mm x 36mm x 22mm (L x W x H)

60W 24V Constant Voltage Non-water proof LED Driver for LED Strip lighting. IP21 hence non-waterproof so suitable for indoor use only. Range of sizes from 60W / 100W / 150W / 360W

60W 24V DC LED Driver / LED Power Supply / LED Transformer - 2.5Amp 2.5A Constant Voltage LED Power Supply IP21 Indoor

- DC Voltage: 24V DC
- Current : 2.5A
- Ripple & Noise: 80MV
- DC Adjustable Range: 10%
- Rated Voltage Voltage Tolerance: 2.0%
- Line Regulation: 0.5%

- Load Regulation: 1% Setup,Rise Time,Hold Up Time:200ms,50ms, 20ms/230VAC AC
- Voltage Range: 190-264VAC
- Frequency Range: 47-63Hz
- Efficiency:85%
- AC Current: 0.4A/230V
- AC Inrush Current: 40A/230V
- Leakage Current< 0.5mA /240VAC
- Over-load: 105%-150% hiccup mode,Auto-recovery
- Over-voltage: 115%-135% Cut Off the Output,Auto-recovery
- Over-temp. : Shut down O/P voltage, Auto-recovery
- Working temp.: -10~ +60C (Refer to output load derating curve)
- Working Humidity:20 ~ 90% RH, non-condensing
- Storage Temp.: -10~ +60C
- Storage Humidity: 10 ~ 95% RH
- Isolation Resistance:I/P-O/P,I/P-FG,O/P-FG:100M Ohms/500VDC / 25C/ 70% RH
- Withstand Voltage: I/P-O/P:3KVAC I/P-FG:1.5KVAC O/P-FG:0.5KVAC

text_attributes

PRODUCT INFORMATION

Warranty	1 Year Warranty
Part L Compliant	No
Dimensions	150mm x 36mm x 22mm
Weight	0.38kg

TECHNICAL SPECIFICATIONS

Power Consumption	60W Max
Input Voltage	110 - 280V AC
Power Factor	>0.95
Operating Temperature	-20°C to 50°C
Ingress Protection	IP21
Output Voltage	24V DC Constant Voltage

AVAILABLE OPTIONS

3-Hour Emergency Version	No
1-10V Dimmable	No
DALI Dimmable	No