[REGISTERED OFFICE ONLY]
The Levels
Capital Business Park
Cardiff
CF3 2PX
02920 099 098
sales@thisiswholesale.co.uk | https://www.onlineb2b.co.uk/

# Suspended Linear LED Direct Indirect Light 1200mm/4ft - RAL Black (4,900lm) 52W Flicker Free

**£132.00**




## Product Description

Suspended Linear LED Light for offices with both direct / indirect illumination. 1200mm / 4ft 52W Suspended Light for office, public open spaces and retail with high lumen output of 4,900 lumens in Natural White 4000K (3800lm:1100lm uplight:downlight). Modern minimalist interior design highly suited by suspended luminaire. Finished in a choice of colours: RAL black or stylish 6063 silver aluminum housing, enclosing an Frosted diffuser for subtle light output suiting a wide range of modern commercial and institutional applications, including hallways, retail & conference rooms. 1200mm linear design with a superior lumen output up to 4,900lm for ample lux levels across a range of environments - can be continious with additional bracket. In-fils available on request. High CRI combined with stylish design make this unit perfectly suited to retail applications. Further options of dimmable: DALI and 1-10V.

DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE

## text_attributes

### PRODUCT INFORMATION

| | |
|---|---|
| LED Type | SMD2835 LEDs |

| | |
|---|---|
| Warranty | 3 Year |
| Part L Compliant | Yes |
| Dimensions | 1178mm x 90mm x 67mm |
| Weight | 3.00kg |
| Equivalent to | 2 x 36W T8 |

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Power Consumption | 52W |
| Input Voltage | 110-280V AC |
| Power Factor | >0.95 |
| Operating Temperature | -20°C to 50°C |
| L70 Rated Lifetime | +45,000hrs |
| Ingress Protection | IP21 |

## LUMEN PERFORMANCE

| | |
|---|---|
| Luminous Efficiency | 95lm/W |
| Beam Angle | 120˚ |
| CRI (Colour Rendering Index) | >80Ra |
| Lumen Output | 4,900lm (3,800lm:1100lm downlight:uplight) |

## AVAILABLE OPTIONS

| | |
|---|---|
| Colour Temperature | Natural White (4000-4500K) |
| 1-10V Dimmable | Available Variant |
| DALI Dimmable | Available Variant |
| DMX 512 Compatible | No |