[REGISTERED OFFICE ONLY]
The Levels
Capital Business Park
Cardiff
CF3 2PX
02920 099 098
sales@thisiswholesale.co.uk | https://www.onlineb2b.co.uk/

LED Premium Street Light 50w c/w Photocell NEMA Dusk til Dawn Sensor Flicker Free

£157.86



Product Description

Fitting Comes inclusive with integral 3-Pin NEMA Socket and Lucy Zodion 70lux Photocell

Luminaire designed for column/post mounting at heights of 4 - 16m, with a range of sizes across 20W - 240W (2,800-33,000lm), IP66 design for exterior environments, with a low profile, sleek silver anodised aluminum body for harsh weather environments, Premium Street light is for urban applications such as car-parks, pathways and pedestrian areas. PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further enhancing this 140lm/W luminaire to give optimum lux levels through out. Furthermore the Premium Street light is compatible with standard mains photocells. Additional benefits include 100,000 hours maintenance free performance, with no-tools/quick release access to the internal control gear for installation. Unit available with either 60mm or 76mm entry bracket for both bottom & side-entry hence universally compatible. Angle of illumination can be adjusted around 10 for increased spread. Slate Grey RAL 7015.

DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE

DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES

DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES

DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES

text_attributes

PRODUCT INFORMATION

Body Colour	Slate Grey RAL 7015
LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	617mm x 212mm x 118mm
Weight	3.85kg
Windage	0.08m²
Socket Type	Optional 3 pin NEMA Socket
Equivalent to	70 SON

TECHNICAL SPECIFICATIONS

Power Consumption	50W
Input Voltage	100-280V AC
Power Factor	>0.96
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+100,000hrs
Ingress Protection	IP66

LUMEN PERFORMANCE

Luminous Efficiency	140lm/W
Beam Angle	150° x 80°
CRI (Colour Rendering Index)	>80Ra
Lumen Output	7,000lm

AVAILABLE OPTIONS

Colour Temperature	3000K (Dark Sky Friendly- 0% ULOR) 4000K
3-Hour Emergency Version	No
Built-in Microwave Occupancy Detector	No
1-10V Dimmable	Available on Request
DALI Dimmable	Available on Request