[REGISTERED OFFICE ONLY]
The Levels
Capital Business Park
Cardiff
CF3 2PX
02920 099 098
sales@thisiswholesale.co.uk | https://www.onlineb2b.co.uk/

6m Black Lamp Post - Flange Plated Bolt Down - RAL9005 Powder Coated Steel Galvanised Street Lamp Post Root Mounted 6 Metre (6m Above Ground)

~~£598.80~~ **£505.80**



Product Description

Flange Plated Lighting Column 6m (Bolt Down) - Steel Galvanised Tubular Street Lamp Post (76mm Shaft / 140mm Base) c/w with door (500mm x 100mm) and wooden backboard/ Column Weight 47kg. Maximum head load (kg/m2) = 20 / 0.40. Hot dipped galvanised. Light duty lighting column suitable for road, residential, CCTV/security features and general amenity areas, with street lanterns, floodlights & post top amenity luminaires (please see related accessories).

PLEASE NOTE - Weight & Windage must be checked for suitability of the column against the installation postcode. Please email us for more information prior to purchase. It is the responsibility of the installer to ensure columns are installed safely and correctly, no liability will be accepted by The LED Store/supplier. In certain cases a ground survey may be required prior to installation.

Requires M16 foundation bolt set & may require template for fitting - items sold separately. Unit does not include column door key. Please see below link to this product.

M8 COLUMN DOOR KEY

Height Above Ground (m)Root (Below Ground) Base Diameter (mm)Shaft Diameter (mm)Base Height (mm)Shaft Height (mm)Max Head Weight kg/m^2Weight (kg)Min Concrete Diameter* (mm)LST-3MCOL3m800mm140mm 76mm1250mm1690mm40kg / 0.427kg950mmLST-4MCOL
4m800mm 140mm 76mm
1250mm
2690mm40kg / 0.432kg950mmLST-5MCOL
5m800mm 140mm
76mm
1250mm
3675mm40kg / 0.437kg525mmLST-6MCOL
6m1000mm 140mm 76mm
1250mm
4660mm40kg / 0.447kg269mmLST-8MCOL
8m1200mm 168mm
89mm
1250mm
6630mm30kg / 0.380kg262mmLST-10MCOL
10m1500mm 168mm
114mm
1250mm
8600mm30kg / 0.28120kg239mmLST-12MCOL12m1700mm 194mm
114mm
1250mm9840mm40kg / 0.33190kg262mm

**Root concrete diameter based on poor soil or better, minimum 230kN/m^2 per m*

Height Above Ground (m)
Flange Plate Size (mm)Base Diameter (mm)
Shaft Diameter (mm)
Base Height (mm)
Shaft Height (mm)Max Head Weight kg/m^2

Weight (kg)Concrete Dimensions* (mm)
LST-3MCOLFP
3m280mm x 280mm140mm
76mm
1250mm
1690mm
40kg / 0.4
30kg700 x 700 x 800
LST-4MCOLFP4m280mm x 280mm
140mm
76mm
1250mm
2690mm
40kg / 0.4
32kg700 x 700 x 800
LST-5MCOLFP5m280mm x 280mm
140mm
76mm
1250mm
3675mm40kg / 0.4
39kg750 x 750 x 800
LST-6MCOLFP6m280mm x 280mm
140mm
76mm
1250mm
4660mm40kg / 0.4
47kg750 x 750 x 800
LST-8MCOLFP8m320mm x 320mm
168mm
89mm
1250mm
6630mm30kg / 0.3
89kg850 x 850 x 900

**Concrete dimensions based on a minimum ground bering pressure of 150kN/m^2 per m (Width x Width x Height)*